



09/10/T2 Light Duty Institutional Casters - 175 LB

- Bright Zinc Plated as standard, Black Electrocoat and Nickel are available as options
- A complete series including Swivel, Rigid and Total Lock casters
- Featuring 1" wide light medium duty wheels
- Double ball raceway swivel
- 5/16" Axle and nut
- NSF Listed

09CL30DR4106YY



T2TP30DH8106YY



09MG30BB8191-0V0000



10PP30DT8106YY



09CT30DB806-0S0000



Wheel Diameter	Overall Height		Swivel Radius				
			#09-Swivel		#T2-Total Lock		
1-5/8"	2-7/16"		1-9/16"				
2"	3"		2-3/32"				
2-1/2"	3-1/4"		2-11/32"				
3"	3-5/8"		2-5/8"		3-15/32"		
4"	4-23/32"		3-1/4"		3-21/32"		
5"	5-5/8"		3-7/8"		3-7/8"		
Plate Code	Overall Size		Bolt Hole Pattern		Mounting Bolt Size		
06	2-3/8" x 3-5/8"		1-3/4" x 2-7/8" slotted 3"		5/16"		
08	1-3/4" x 3"		1" x 2-3/16" slotted to 2-5/16"				
S8	1-3/4" x 3"		1" x 2-1/8" slotted to 2-5/16"		1/4"		
P2	2-3/8" x 2-3/8"		1-3/4" x 1-3/4"		3/16"		
Stem Code	Size	Stem Type	Stem Code	Size	Stem Type		
31	5/16" - 18 x 2"	Threaded			Round Expandable Adaptor Stem		
60	3/8" - 16 x 3/4"		71	0.720" - 0.851"			
61	3/8" - 16 x 1"		72	0.852" - 0.927"			
62	3/8" - 16 x 1-1/2"		7S	0.920" - 0.980"			
64	3/8" - 16 x 1-3/8"		73	0.928" - 1.029"			
79	7/16" - 14 x 2-1/4"		7A	1.020" - 1.100"			
33	7/16" - 14 x 1-1/2"		74	1.110" - 1.180"			
66	1/2" - 13 x 3/4"		75	1.360" - 1.425"			
67	1/2" - 13 x 1"		76	1.426" - 1.589"			
68	1/2" - 13 x 1-1/2"		77	1.790" - 1.850"			
6M	1/2" - 13 X 1-9/16"		R1	0.720" - 0.851"		Square Expandable Adaptor Stem	
70	1/2" - 13 x 2-3/4"		R2	0.852" - 0.927"			
86	7/16" ID, for Pipe w/ 1" O.D.		Pipe Thread (NPT34)	R3			0.928" - 1.029"
				R4			1.030" - 1.140"
53	7/16" x 7/8"	R5	1.360" - 1.425"				
90	7/16" x 1-3/16"	R6	1.426" - 1.589"				
91	7/16" x 1-3/8"	Grip Ring	R7	1.790" - 1.850"			
			L1	5/16" x 5-3/4"	Ladder Stem(not including Spring)		
			49	7/16" x 1-3/4"			
97	7/16" x 2"		42	7/8"	Octagon w/ 5/16" Cross drilled Hole		

09/10/T2 SERIES • CAPACITY 175



Wheel Dia.	Tread Width	Wheel Type	Load Capacity	Bearing Type	Replace ** with desired fastening options			+Color
					Swivel Part #	Rigid Part #	Total-Lock Part #	
1-5/8"	7/8"	Yoke and axle/nut			09ZZ16DZ81ZZYAN	10ZZ16DZ81ZZYAN	T2ZZ16DZ81**YY	
		Thermo-Pro™	80	Precision	09TP16DI41**YY	10TP16DI41**YY	T2TP16DZ81**YY	
		Poly-Pro™	100		09PP16DL41**YY	10PP16DL41**YY	T2PP16DZ81**YY	
2"	1"	Yoke and axle/nut			09ZZ20DZ81ZZYAN	10ZZ20DZ81ZZYAN	T2ZZ20DZ81**YY	
		Poly-Pro™	150	Precision	09PP20DL41**YY	10PP20DL41**YY	T2PP20DZ81**YY	
2-1/2"	1"	Yoke and axle/nut			09ZZ25DZ81ZZYAN	10ZZ25DZ81ZZYAN	T2ZZ25DZ81**YY	
		Thermo-Pro™	110	Precision	09TP25DI41**YY	10TP25DI41**YY	T2TP25DI81**YY	
		Poly-Pro™	150		09PP25DL41**YY	10PP25DL41**YY	T2PP25DL81**YY	
3"	1"	Yoke and axle/nut			09ZZ30DZ81**YAN	10ZZ30DZ81**YAN	T2ZZ30DZ81**YAN	
		Hard Rubber	125	Plain	09HR30DB81**YY	10HR30DB81**YY	T2HR30DB81**YY	
		Polyolefin	175	Plain	09PO30DB81**YY	10PO30DB81**YY	T2PO30DB81**YY	
		Poly-Pro™	125	Plain	09PP30DT81**YY	10PP30DT81**YY	T2PP30DT81**YY	
			150	Precision	09PP30DI41**YY	10PP30GI41**YY	T2PP30GI41**YY	
		Soft Rubber	100	Plain	09SR30DB81**YY	10SR30DB81**YY	T2SR30DB81**YY	
		Thermo-Pro™	120	Plain	09TP30D+81**YY	10TP30D+81**YY	T2TP30D+81**YY	H,T
			120	Precision	09TP30DI41**YY	10TP30DI41**YY	T2TP30DI41**YY	
		Crystalic™	120	Precision	09CL30DR41**YY	10CL30DR41**YY	T2CL30DR41**YY	
MAG-Solid PU Tread	150	Plain	09MG30BB81**YY	10MG30BB81**YY	T2MG30BB81**YY			
4"	1"	Yoke and axle/nut			09ZZ40DZ81**YAN	10ZZ40DZ81**YAN	T2ZZ40DZ81**YAN	
		Hard Rubber	140	Plain	09HR40DB81**YY	10HR40DB81**YY	T2HR40DB81**YY	
		Polyolefin	175	Plain	09PO40DB81**YY	10PO40DB81**YY	T2PO40DB81**YY	
		Poly-Pro™	140	Plain	09PP40DT81**YY	10PP40DT81**YY	T2PP40DT81**YY	
			150	Precision	09PP40DI41**YY	10PP40GI41**YY	T2PP40GI41**YY	
		Soft Rubber	125	Plain	09SR40DB81**YY	10SR40DB81**YY	T2SR40DB81**YY	
		Thermo-Pro™	125	Plain	09TP40D+81**YY	10TP40D+81**YY	T2TP40D+81**YY	H,T
			125	Precision	09TP40DI41**YY	10TP40DI41**YY	T2TP40DI41**YY	
Crystalic™	125	Precision	09CL40DR41**YY	10CL40DR41**YY	T2CL40DR41**YY			
5"	1"	Yoke and axle/nut			09ZZ50DZ81**YAN	10ZZ50DZ81**YAN	T2ZZ50DZ81**YAN	
		Hard Rubber	145	Plain	09HR50DB81**YY	10HR50DB81**YY	T2HR50DB81**YY	
		Polyolefin	175	Plain	09PO50DB81**YY	10PO50DB81**YY	T2PO50DB81**YY	
		Poly-Pro™	145	Plain	09PP50DT81**YY	10PP50DT81**YY	T2PP50DT81**YY	
		Soft Rubber	125	Plain	09SR50DB81**YY	10SR50DB81**YY	T2SR50DB81**YY	
		Thermo-Pro™	135	Plain	09TP50D+81**YY	10TP50D+81**YY	T2TP50D+81**YY	

* Reduce OAH by 3/32" for stem casters.