



SEMI-STEEL WHEEL

- Precisely machined Semi-Steel wheels
- Temperature range: -45°F to 800°F
- Tensile strength of 30,000PSI
- Hardness: Brinell 145

SS60JS04



SS60LS69



Wheel Dia	Tread Width	Hub Length	Load Capacity	Hub Design type	Bore I.D.	Replace ** with desired bearing code				Part Number
						Roller BRG	Sealed Ball BRG	Delrin BRG	Bronze BRG	
2"	1"	1-1/8"	250	C	1/4"					SS20DS80
2-1/2"	1"	1-1/8"	250	C	5/16"					SS25DS81
3"	1-1/4"	1-9/16"	350	C3	3/8"					SS30GS82
3"	1-1/4"	1-9/16"	350	C3	1/2"					SS30GS83
3-1/2"	1-1/4"	1-9/16"	400	C3	3/8"					SS35GS82
4"	1-1/4"	1-9/16"	350	C3	3/8"					SS40GS82
4"	1-1/4"	1-9/16"	350	C3	1/2"					SS40GS83
5"	1-1/4"	1-9/16"	350	C3	3/8"					SS50GS82
5"	1-1/4"	1-9/16"	350	C3	1/2"					SS50GS83
3-1/4"	1-1/2"	1-5/8"	400	C	1-3/16"					SS34HS84
		1-7/8"			1/2"	92~	6M	12, 56	SS34HS**	
					5/8"	01				
					3/4"	03		11, 57		
3-1/4"	2"	2-3/16"	700	C	1-3/16"					SS34JS84
		2-7/16"			1/2"	92~	60	12, 56	SS34JS**	
					5/8"	02				
					3/4"	04, 09		11, 57		B1, B5
4"	1-1/2"	1-5/8"	600	C4	1/2"				SS40HS83	
4"	1-1/2"	1-5/8"	600	C4	1-3/16"					SS40HS84
		1-7/8"			1/2"	92~	6M	12, 56	SS40HS**	
					5/8"	01				
					3/4"	03		11, 57		
4"	2"	2-3/16"	700	C3	1-3/16"					SS40JS84
		2-7/16"			1/2"	92~	60	12, 56	SS40JS**	
					5/8"	02				
					3/4"	04, 09		11, 57		B1, B5



Wheel Dia	Tread Width	Hub Length	Load Capacity	Hub Design type	Bore I.D.	Replace ** with desired bearing code				Part Number
						Roller BRG	Sealed Ball BRG	Delrin BRG	Bronze BRG	
5"	1-1/2"	1-5/8"	600	C4	1-3/16"					SS50HS84
		1-7/8"			1/2"	92~	6M	12, 56		SS50HS**
					5/8"	01				
					3/4"	03		11, 57		
5"	2"	2-3/16"	1000	C	1-3/16"					SS50JS84
		2-7/16"			1/2"	92~	60	12, 56		SS50JS**
					5/8"	02				
					3/4"	04, 09		11, 57	B1, B5	
6"	1-1/2"	1-5/8"	600	C5	1-3/16"					SS60HS84
		1-7/8"			1/2"	92~	6M	12, 56		SS60HS**
					5/8"	01				
					3/4"	03		11, 57		
6"	2"	2-3/16"	1000	C4	1-3/16"					SS60JS84
		2-7/16"			1/2"	92~	60	12, 56		SS60JS**
					5/8"	02				
					3/4"	04, 09		11, 57	B1, B5	
6"	2-1/2"	2-3/4"	1600	C5	1-3/16"	92~				SS60KS84
		3"			06					SS60KS06
6"	2-1/2"	2-3/4"	1800	C5	1-15/16"					SS60KS85
		3"			3/4"	93~	89			SS60KS**
					1"	23		58	B7	
					1-1/4"	25				
6"	2-1/2"	3-1/4"	1800	S4	1-15/16"					SS60QS85
		3-1/2"			3/4"	93~	69			SS60QS**
					1"	24	71P		B8	
					1-1/4"	26				
6"	3"	3-1/4"	2700	C5	1-15/16"					SS60LS85
		3-1/2"			3/4"	93~	69			SS60LS**
					1"	24	71P		B8	
					1-1/4"	26				
8"	2"	2-3/16"	1400	C6	1-3/16"					SS80JS84
		2-7/16"			1/2"	92~	60	12, 56		SS80JS**
					5/8"	02				
					3/4"	04, 09		11, 57	B1, B5	
8"	2-1/2"	2-3/4"	1600	S6	1-3/16"	92~				SS80KS84
		3"			06					SS80KS06
8"	2-1/2"	2-3/4"	1800	S6	1-15/16"					SS80KS85
		3"			3/4"	93~	89			SS80KS**
					1"	23		58	B7	
					1-1/4"	25				
8"	2-1/2"	3-1/4"	1800	S6	1-15/16"					SS80QS85
		3-1/2"			3/4"	93~	69			SS80QS**
					1"	24	71P		B8	
					1-1/4"	26				
8"	3"	3-1/4"	2500	S6	1-15/16"					SS80LS85
		3-1/2"			3/4"	93~	69			SS80LS**
					1"	24	71P		B8	
					1-1/4"	26				
10"	2-1/2"	2-3/4"	1700	S5	1-3/16"	92~				SS10KS84
		3"			06					SS10KS06
10"	2-1/2"	2-3/4"	2000	S5	1-15/16"					SS10KS85
		3"			3/4"	93~	89			SS10KS**
					1"	23		58	B7	
					1-1/4"	25				
10"	2-1/2"	3-1/4"	2000	S5	1-15/16"					SS10QS85
		3-1/2"			3/4"	93~	69			SS10QS**
					1"	24	71P		B8	
					1-1/4"	26				
10"	3"	3-1/4"	2500	S5	1-15/16"					SS10LS85
		3-1/2"			3/4"	93~	69			SS10LS**
					1"	24	71P		B8	
					1-1/4"	26				
12"	2-1/2"	2-3/4"	2000	S5	1-15/16"					SS12KS85
		3"			3/4"	93~	89			SS12KS**
					1"	23		58	B7	
					1-1/4"	25				
12"	2-1/2"	3-1/4"	2000	S5	1-15/16"					SS12QS85
		3-1/2"			3/4"	93~	69			SS12QS**
					1"	24	71P		B8	
					1-1/4"	26				
12"	3"	3-1/4"	2500	S5	1-15/16"					SS12LS85
		3-1/2"			3/4"	93~	69			SS12LS**
					1"	24	71P		B8	
					1-1/4"	26				

~ including spanner bushing